



SNYPER-LTE+ (EU)

4G/LTE, 3G/UMTS & 2G/GSM Network Signal Analyser



General Description

The SNYPER-LTE+ (EU) is a high performance, multi-language network signal analyser dedicated to surveying the 4G/LTE(EU), 3G/UMTS & 2G/GSM European networks.* It comes in a robust carrycase with antennas, a USB cable, a USB car charger, and power accessories.

It incorporates a number of important features and can perform four types of survey: 4G/LTE, 3G/UMTS, 2G/GSM and a combined 4G/3G/2G survey. The combined 4G/3G/2G survey will provide multiple results from each network operator, in one single survey.

The powerful SNYPER summary page displays percentage thresholds to determine the most suitable mobile network operator available and the performance of a "preferred" MNO can be evaluated against the other networks.

The SNYPER can also be used to help establish optimum antenna placement and perform local site surveys.


*SNYPER-LTE+ (EU) does not require a SIM in order to function.

Features

| | | | | | | | |
|----------------|----------------|------------------|----------------|------------------|---------------------|--------------------|-------------|
| 2G GSM | 3G UMTS | 4G LTE | EU Coverage | | | | |
| USB Power | USB Serial | HTML Reports | CSV Reports | MAP Portal | GEAR Accessories | HARD Carry Case | |
| TFT Display | 2Ah Battery | Win Linux/Mac | MNO Summary | SAVE 1 Survey | MULTI Language | -10 +50 deg C | SIM Free |

Featured Applications

- » Enhanced cellular surveying of new and existing installations on 4G, 3G and 2G networks
- » Establish most suitable operator for application
- » Evaluate your "preferred" MNO's performance
- » Determine optimum antenna placement
- » Results are reported in CSV & graphical HTML format





SNYPER-LTE+ (EU)

4G/LTE, 3G/UMTS & 2G/GSM Network Signal Analyser

General Features

- » 2 Supported Bands GSM | GPRS:
900/1800MHz
- » 2 Supported Bands UMTS/HSPA+:
900/2100MHz
- » 5 Supported Bands LTE:
800/900/1800/2100/2600MHz
- » Blue antenna for 700MHz to 2300 MHz
- » Silver/Grey Antenna for 2600MHz
- » Large easy to read LCD display
- » No SIM required for operation
- » Logical menus and operation
- » Long life rechargeable battery
- » 0.5m USB Cable for charging and downloads to PC
- » USB car charger included
- » Rugged and durable construction
- » Supplied in a robust carry case
- » Multiple language support
(English/French/German/Italian/Spanish)

Interfaces

- » 1 x USB 2.0 FS(12 MBits/s) for PC interface and for battery charging
- » 1 x SMA female cellular antenna connector
- » Red LED charging indicator
- » Display: 2.4" Diagonal QVGA 240 x 320 RGB TFT with LED backlight
- » Display: 80 degree viewing angle
- » Display Brightness: 500md/m2

Power Supply

- » Mains Input: 100-240V 50/60Hz
- » Multi-region Heads: UK / EU /US / AU
- » Charger O/P: 5V DC 2000mA

Approvals and Compliance

- » CE

Environmental

- » Dimensions
SNYPER: 141mm x 76mm x 36mm
Antenna: 78mm x 11mm
- » Weight
Without antenna: 200 grams
With supplied antenna: 207 grams
- » Operating Temperature Range: -10 to +50 deg C
- » Storage Temperature Range: -20 to +50 deg C
- » Operating Humidity Range: 20 to 85% RH Non-condensing
- » Battery: Lithium Ion 3.7V, 2000mAh
- » Life: 48 hours based on 20 surveys /day at room temperature with auto power off enabled
- » Warm up time: 2s

Reporting

HTML Reporting

- » Graphical display ordered by signal strength
- » Listing of advanced cellular parameters
- » Complete summary breakdown for all recorded cells
- » Recorded survey date and time
- » Access to Siretta's mapping portal for survey storage and base-station mapping (Registration Required)

CSV Reporting

- » Complete survey breakdown for each recorded cell
- » Listing of advanced cellular parameters

Product Option

As an alternative to the SNYPER-LTE+ (EU) with its carry case and full accessories, there is also available the SNYPER-LTE+ (EU) (Analyser Only)

Excludes robust carry case and some accessories

Includes:

- » SNYPER-LTE+ (EU) Analyser
- » Two omni-directional antennas
- » 0.5m USB charging/download cable

Contact your Siretta representative for more details