

# LP[G]AM-BC3G-26

Low Profile MiMo Cellular Antenna

PANORAMA ANTENNAS

24/06/2016 v.1

## Low Profile MiMo Cellular Antenna with optional GPS/GNSS

Panel mount

2 x 2 Cellular /LTE MiMo and optional GPS/GNSS

Robust and cost effective solution for M2M and IOT applications




The LP[G]AM-BC3G-26 range has been designed to provide MiMo Cellular / LTE antenna function for IOT and M2M applications. The compact, robust low-profile housing is weatherproof and contains two antenna elements with effective isolation and correlation covering all current global cellular and LTE bands in freq. range 698-960/1710-3800MHz. The LG version includes an active GPS/GNSS/Galileo/Beidou antenna for applications which require position or timing function.

The antenna can be fitted on a non-conductive panel if required\* and offers easy, quick, secure and weatherproof installation with the single hole mounting bush and acrylic adhesive sealing pad. Supplied with integrated 3m (10') cables and SMA plug connectors, the antenna will offer plug and play connectivity with many different terminals.

\* Performance may change depending on mounting position/surface.

### Technical Drawing


LGAM-BC3G-26-3SP shown



Part No.		LPAM-BC3G-26-3SP	LGAM-BC3G-26-3SP
<b>Electrical Data</b>			
Frequency Range (MHz)	Elements 1 & 2	698-960 / 1710-3800	
	Element 3	-	1562-1612MHz
Peak Gain: Isotropic †	Element 1 & 2: 698-960MHz	1.5dBi	
	Elements 1 & 2: 1710-2170MHz	4.5dBi	
	Elements 1 & 2: 2500-3800MHz	5dBi	
Pattern	Omni-directional		
Nominal Impedance	50Ω		
Max input power (W)	20		
<b>GPS/GNSS Data</b>			
Frequency Range (MHz)	-	1562-1612MHz	
LNA Gain (dB)	-	26	
Polarisation	-	Right Hand Circular	
Operating Voltage	-	3-5VDC (Fed via Coax)	
Current	-	Typical <20mA	
<b>Mechanical Data</b>			
Dimensions (mm)	Height	49 (1.92")	
	Length	150 (5.90")	
	Width	45 (1.77")	
Operating Temp (°C)	-30° / +70°C (-30° / 158°F)		
Material	UV Stable ABS Plastic		
Colour	Black		
Typical Weight (g)	337		
<b>Mounting Data</b>			
Fixing	18mm (3/4") mounting bush and acrylic adhesive pad		
<b>Cable Data</b>			
Elements 1 & 2: Cell / LTE	Cable Type	RG174	
	Diameter (mm)	2.8 (0.1")	
	Length (m)	3 ( 9.8')	
	Termination	2x SMA Plugs	
Element 3: GPS/GNSS	Cable Type	-	RG174
	Diameter (mm)	-	2.8 (0.1")
	Length (m)	-	3 ( 9.8')
	Termination	-	SMA Plug


† Peak gain simulated off a groundplane and does not include cable attenuation

Typical VSWR - Elements 1&2\*



\* VSWR measured with 3m (10') of RG174 cable Green and Red Plots = Elements 1&2 in free space Black and Blue plots = Elements 1&2 on a 400x400mm ground plane


Typical Isolation - Elements 1&2\*



\*Isolation measured with 3m (10') of RG174 cable Red Plot = mounted on a 400x 400mm (1' 4" x 1'4") ground plane Green Plot = free space

Typical Radiation Pattern -GPS/GNSS Element 3

Element 3: Typical E Plane Pattern (1602MHz)




Typical 3D Radiation Patterns - Cell / LTE Elements 1&2


3D Gain Plot Side (700MHz)




3D Gain Plot Top (700MHz)




3D Gain Plot Side (800MHz)




3D Gain Plot Top (800MHz)




3D Gain Plot Side (900MHz)




3D Gain Plot Top (900MHz)




3D Gain Plot Side (1800MHz)




3D Gain Plot Top (1800MHz)




3D Gain Plot Side (2100MHz)




3D Gain Plot Top (2100MHz)




3D Gain Plot Side (2600MHz)




3D Gain Plot Top (2600MHz)



3D Gain Plot Side (3600MHz)



3D Gain Plot Top (3600MHz)



\*3D radiation patterns simulated in CST Microwave Studio on a 600x600mm (2' X2') ground plane with both elements fed together.  
 † Element 1&2 Patterns simulated in CST Microwave Studio in free space excluding cable loss. Element 3 pattern measured in free space.

**PANORAMA ANTENNAS**  
 Panorama Antennas Ltd  
 Frogmore, London, SW18 1HF, United Kingdom

T: +44 (0)20 8877 4444  
 F: +44 (0)20 8877 4477  
 E: sales@panorama-antennas.com  
 www.panorama-antennas.com

Waiver: The data given above is indicative of the performance of the product/s under particular conditions and does not imply a guarantee of performance. These specifications are subject to change without notice.  
 Copyright © Panorama Antennas Ltd. All rights reserved.