



CONNECTED • SECURE • LIVE

CSL SIGNAL ANALYSER

The Perfect Solution for your Connected Device



KEY FEATURES

- Ideal for deploying any mobile application
- Live monitor function to find the optimum installation location (SIM required for 4G)
- 4G versions are backwards compatible (2G/3G/4G)
- 2.4Ghz (4G version only)
- Rechargeable battery with up to 20-hour life and additional battery saving options
- Multilingual - 11 languages
- Download survey results and live monitor results via USB
- Rain resistant material and durable protective cover provided
- Automatic power down when not in use

SPECIFICATION

Model	CS2369 (2G/GSM) & CS2389 (2G/GSM, 3G/UMTS, 4G/LTE)
Dimensions	172mm (h) x 72mm (w) x 20mm (d)
Weight	149g including aerial
Temperature	-20°C to +60°C transit, -4°C to +40°C operating
Humidity	0-80% non-condensing
Warranty	2 years
Radio Technology	2G/GSM, 3G/UMTS, 4G/LTE (depending on version) 2.4Ghz
Battery	3.7 Volt 1000mAh
Aerial	SMA Male connector
Charger	5 Vdc micro USB plug-top charger or equivalent
Screen Size	2.8 inch (7.1cm)
Screen Resolution	320 x 240
Screen Type	Resistive touch screen
Memory	Holds up to 240 surveys
Languages	English, German, Spanish, Italian, French, Danish, Dutch, Finnish, Czech, Portuguese, Swedish
Approval	CE

BANDS

Part Number	CS2369	CS2389
4G (LTE) Bands (MHz)		800 (B20), 900 (B8), 1800 (B3), 2100 (B1), 2600 (B7)
3G (UMTS) Bands (MHz)		900 (B8), 2100 (B2)
2G (GSM) Bands (MHz)	850 (B5), 900 (B8), 1800 (B3), 1900 (B2)	900 (B8), 1800 (B3)
WiFi		2.4Ghz